

OilShield HD Hose Reels (Single Arm)

Oilshield heavy duty retractable hose air reel is constructed with powder coated 18 gauge heavy duty steel and have 12 pt. Ratchet Locking Mechanism. It comes with the oil resistant, lightest, strongest and most flexible OilShield air hose. This combo is perfect for Automotive & DIY Industry. It is a great cost-effective alternative to motor driven reels.

Features

- Unmatched 2 year warranty
- 12 point ratchet system which helps lock out the hose at shorter lengths
- Can also be mounted on wall, ceiling or floor, trucks and trailers
- Specialised internal system reduces the spring vibration, enables quitter operations & extends the life of spring
- Includes 3' Lead-in hose
- Heavy duty 18 gauge powder coated steel construction

Hose Features

- 3 year limited warranty
- RMA Class A oil resistant core tube and cover
- Resists welding spatters and grinding sparks
- 100% rubber construction
- 30% lighter hose than standard rubber air hoses in same class
- Solid Brass fittings superior than aircraft aluminium
- High strength polyester woven braided reinforcement
- 300 PSI working pressure
- 4:1 Safety factor
- Maintains integrity under extreme weather conditions
- Flexibility from -30°F to +190°F
- Ozone resistant
- Abrasion resistant
- Kink Resistant
- 4 finger grip bend restrictor for better use & easier control over the hose.



Constructed with 18 gauge heavy duty steel & with ribbed edges, our air hose reel ensures strength, durability and operator safety! it provides stability and reliability in any environment.

<div>300 PSI</div> <div>Working Pressure</div>	<div>4:1</div> <div>Safety Factor</div>	<div>2 Year</div> <div>Warranty on</div> <div>Reel</div> <div>3 Year Warranty on Hose</div>	<div>-50°F to 190°F</div> <div>Temperature Range</div>
--	---	---	--

Variations


Medium

Part No.	Inner Diameter (Inch)	Length (Feet)	Inlet Fitting (Inch)	Outlet Fitting (Inch)	Lead-in Hose (Feet)	Package Dimensions L x W x H (Inch)	Package Weight (Pounds)
OSRHD3850	3/8	50	3/8 Male	3/8 Male	3	17.00 x 9.00 x 19.00	34.100
OSRHD1250	1/2	50	1/2 Male	1/2 Male	3	17.00 x 9.00 x 19.00	33.000

Large

Part No.	Inner Diameter (Inch)	Length (Feet)	Inlet Fitting (Inch)	Outlet Fitting (Inch)	Lead-in Hose (Feet)	Package Dimensions L x W x H (Inch)	Package Weight (Pounds)
OSRHD3875	3/8	75	3/8 Male	3/8 Male	3	20.50 x 9.25 x 22.00	
OSRHD1265	1/2	65	1/2 Male	1/2 Male	3	20.50 x 9.25 x 22.00	

Product Images



This PDF was downloaded from the following URL
<https://www.rmwind.com/reel/oilshield-heavy-duty-hose-reel-single-arm/?®ion=north-america>
 on Sunday, 14 December 2025

Scan QR Code on the right to access this URL in the browser.

