

Hose Barbs

A barb (or hose barb), which connects flexible hose or tubing to pipes, typically has a male-threaded end which mates with female threads. The other end of the fitting has a single- or multi-barbed tube—a long tapered cone with ridges, which is inserted into a flexible hose.

- Features
- Solid Heavy-Duty Brass Construction
  - Must be fastened with hose clamps or ferrules.
  - Use to attach a low pressure fluid or pneumatic hose to another fitting or machine.



Variations

Part No.	Description	NPT	Package Dimensions L x W x H (Inch)	Package Weight (Pounds)
ALF-7001-1	2 pc. 1/4 I.D. x 1/4 in. MNPT	1/4	x x	
ALF-7002-1	2 pc. 3/8 I.D. x 1/4 in. MNPT	1/4	x x	
ALF-7003-1	2 pc. 3/8 I.D. x 3/8 in. MNPT	3/8	x x	
ALF-7004-1	2 pc. 1/2 I.D. x 3/8 in. MNPT	3/8	x x	
ALF-7005-1	2 pc. 1/2 I.D. x 1/2 in. MNPT	1/2	x x	

Product Images





This PDF was downloaded from the following URL  
<https://www.rmwind.com/fitting/hose-barbs/?&region=north-america>  
on Thursday, 28 August 2025

Scan QR Code on the right to access this URL in the browser.

