

OilShield Snubber Air Hoses

The Oil-Shield Snubber hose is the perfect accessory for your shop. It helps keep the supply hose on the ground and helps prevent a tripping hazard in the shop. The Oil-Shield Snubber hose is made from the same award-winning Oil-Shield hose. It also carries the Class A Oil resistance rating. Put one of the Oil-Shield snubber hoses on each tool and make changing out tools quicker and easier as well as keeping your shop safer.

Features

- Covered by a 90 day material and workmanship warranty
- Solid Brass fittings superior than aircraft aluminium
- 360° ball swivel reduces twisting and kinking of hose
- RMA Class A oil resistant core tube and cover
- Resists welding spatters and grinding sparks
- 100% rubber construction
- 30% lighter hose than standard rubber air hoses in same class
- High strength polyester woven braided reinforcement
- 300 PSI working pressure
- 4:1 Safety factor
- Maintains integrity under extreme weather conditions
- Flexibility from -30°F to +190°F
- Ozone resistant
- Abrasion resistant
- Kink Resistant
- 4 finger grip bend restrictor for better use & easier control over the hose.



Absorbs shock to air couplers from pneumatic tools

300 PSI
Working Pressure

4:1
Safety Factor

-50° to 190°F
Temperature Range

90 days
Warranty

Features at a glance




Shock Absorbant Hose

Snubber Hose is a shorter piece of hose designed to absorb shock to air couplers from impact tools & air hammers. It helps the hose to lay flat on the ground & prevent tripping hazards.



360° ball swivel Revolving fitting

Revolving fitting extends hose life by preventing excessive hose bending & stress, eliminating kinks in supply lines, reduce maintenance frequency & increase air tool manoeuvrability



Polyester braided reinforcement.

High strength polyester braided reinforcement Construction to prevent elongation of hose. Industrial thread and yarn add superior strength with 300 PSI working pressure with 4:1 safety factor.



Four finger grip bend restrictor

Blubird rubber Air Hose comes with four finger grip bend restrictor which increase the working efficiency of user. It reduce bending stress near the hose-coupling junction & prevent it from kinks.

Variations

Snubber Hose

Part No.	Inner Diameter (Inch)	Length (Feet)	Fittings (Inch)	Package Dimensions L x W x H (Inch)	Package Weight (Pounds)
OSSR1202	1/2	2	1/2 Male NPT w/ 360 degree Ball Swivel x 1/2 Female NPT	12.00 x 8.00 x 1.50	0.770
OSSR1205	1/2	5	1/2 Male NPT w/ 360 degree Ball Swivel x 1/2 Female NPT	12.00 x 8.00 x 2.25	1.050
OSSR3802	3/8	2	1/4 Male NPT w/ 360 degree Ball Swivel x 1/4 Female NPT	12.00 x 8.00 x 1.50	5.450
OSSR3805	3/8	5	1/4 Male NPT w/ 360 degree Ball Swivel x 1/4 Female NPT	12.00 x 8.00 x 2.00	0.870

Product Images



This PDF was downloaded from the following URL
<https://www.rmwind.com/hose/oilshield-snubber-air-hose/?®ion=north-america>
 on Thursday, 09 July 2026

Scan QR Code on the right to access this URL in the browser.

