



# BluBird Rubber Air Hoses

Designed to offer the best of both worlds – the exceptional cold weather flexibility, durability & premium feel of high-end rubber hoses & the light-weight, comfort of premium hybrid hoses.

#### **Features**

- 10 year limited warranty
- 100% rubber construction
- 40% lighter hose than standard rubber air hoses
- Solid Brass fittings superior than aircraft aluminium
- High strength polyester woven braided reinforcement
- 300 PSI working pressure
- 4:1 Safety factor
- Maintains integrity under extreme weather conditions
- Flexibility from -50°F to +190°F
- Ozone resistant
- Abrasion resistant
- Kink Resistant
- 4 finger grip bend restrictor for better use & easier control over the hose.

40% Lightest, Strongest & Most Flexible Rubber Air Hose Technology



300 PSI Working Pressure

4: I Safety Factor 10 Year

-50° F to 190°F

Temperature Range

# Features at a glance



## Lightest | Strongest | Most Flexible

40% Lighter than other Rubber Air Hoses, constructed with abrasion-resistant exterior cover & polyester braided reinforcement from inside. Durability in extreme conditions from -50° to 190 °F.



#### Polyester braided reinforcement.

High strength polyester braided reinforcement construction to prevent elongation of hose. Industrial thread and yarn add superior strength with 300 PSI working pressure for 4:1 safety factor.



#### Four finger grip bend restrictor

Blubird rubber Air Hoses comes with four finger grip bend restrictors which increase the working efficiency of user. It reduce bending stress near the hose-coupling junction & prevents it from kinks.



#### Temperature flexibility

Utmost hot & cold environments are a challenge for all rubber hoses but Blubird rubber air hose have flexibility to handle hot weather temperature upto 190°F and cold weather temperature upto -50°F.





# **Variations**

# General Purpose Air Hose

Part No.	Inner Diameter (Inch)	Length (Feet)	Fittings (Inch)	Package Dimensions L x W x H (Inch)	Package Weight (Pounds)
BB1425	1/4	25	1/4 NPT	7.00 x 7.00 x 3.00	1.930
BB1450	1/4	50	1/4 Male NPT	9.50 x 9.50 x 3.50	3.690
BB14100	1/4	100	1/4 Male NPT	13.25 x 13.25 x 3.75	7.400
BB3825	3/8	25	1/4 Male NPT	10.00 x 10.00 x 2.75	2.690
BB3835	3/8	35	1/4 Male NPT	9.50 x 9.50 x 3.50	3.950
BB3850	3/8	50	1/4 Male NPT	10.25 x 10.25 x 4.50	5.280
BB38100	3/8	100	1/4 Male NPT	12.25 x 12.25 x 5.50	10.660
BB1225	1/2	25	1/2 NPT w/ 3/8 NPT reducer	10.75 x 10.75 x 4.00	3.700
BB1250	1/2	50	1/2 NPT w/ 3/8 NPT reducer	10.75 x 10.75 x 4.80	7.500
BB12100	1/2	100	1/2 NPT w/ 3/8 NPT reducer	13.00 x 13.00 x 6.75	13.790
BB3450	3/4	50	3/4 Male NPT	17.00 x 17.00 x 6.00	15.620

#### **Extension Air Hose**

Part No.	Inner Diameter (Inch)	Length (Feet)	Fittings (Inch)	Package Dimensions L x W x H (Inch)	Package Weight (Pounds)
BB3815	3/8	15	1/4 Male NPT	9.00 x 9.00 x 3.00	1.650
BB1210	1/2	10	1/2 Male NPT	10.00 x 10.00 x 3.00	1.780
BB1215	1/2	15	1/2 Male NPT	10.50 x 10.50 x 3.50	2.260

# **Product Images**

















# **Videos**



Blubird Technology November 10, 2014 7:29





Blubird Air Hose May 17, 2021 1:58





Blubird Fastfix September 19, 2017 3:18






Blubird Fleet Edition September 20, 2017 3:07



### **Related Products**



# Blubird Air Hose Reels (Single Arm)







### Hose Reel Cart

Heavy-duty Garden Hose Reel Cart holds 400 feet of 5/8in. garden hose (not included). Features strong tubular steel frame and foam-padded handle. Rolls easily on 10in. pneumatic tires with solid steel axles. Built-in basket for accessories.





#### HF1 Blow Gun with Hush Tech Nozzle

Blubird Blow Guns feature an ergonomically superior gun body for maximum comfort and control which reduces operator fatigue. A variable flow trigger regulates air volume precisely with maximum flow, equal to or greater than the competition. The exclusive modular accessories system allows the Blubird blow guns to be customized for extension length and tips needed for any job.









Industrial "M" Style Couplers & Plugs

1/4" MNPT M style couplers are easy to use; simply push plug into coupler to engage, pull sleeve back to remove. Features a steel drag guard to prevent accidental uncoupling. M style couplers have a 1/4" basic flow size and air flow of 35 SCFM. Maximum inlet pressure of 300 PSI. 1/4" M style MNPT plugs are the industry standard style plugs. These steel plugs have a 1/4" basic flow size, maximum air flow of 40 SCFM and a maximum inlet pressure of 300 PSI.





This PDF was downloaded from the following URL https://www.rmxind.com/hose/blubird-rubber-air-hoses/?&region=north-america on Wednesday, 30 April 2025

Scan QR Code on the right to access this URL in the browser.

