

## OilShield Fuel Hoses

RMX Oil Shield synthetic yarn farm fuel transfer hose assembly with static wire required for use with or 0 volt "Electric" pumps. 2X Kink Resistant and Flexible down to -30°F. Award Winning Formulation. Construction: oil resistant tube/cover. Spiral reinforced with synthetic yarn. Includes static wire built into hose wall.

### Features

- 1 year warranty
- Nitro cover
- 8" Internal strain relief springs on each end to prevent kinking at the coupling
- 2x kink resistant than other fuel hoses
- RMA Class A oil-resistant tube & cover
- Static wire allows use with electric pumps
- Cold weather flexibility down to -30° F
- 100 PSI working pressure
- Ozone resistant
- Kink resistant
- For use where UL approval is not required

For use with diesel, gasoline, kerosene, biodiesel B10 and B20



1 Year  
Warranty

Class A Oil  
Resistant

100 PSI  
Working Pressure

-30°F  
Temperature Range

### Features at a glance



#### Internal strain relief springs

Internal strain relief springs eliminate your hose from kinking, crimping, and straining at the faucet. Heavy-duty spring coil allows your hose to bend but not kink, protecting your hose and faucet.




#### RMA Class A Oil-resistant

Oil-Shield fuel hose is perfect for work areas where oil, diesel, grease spillage is a concern. It can remain in constant contact with fuel & oil for months & functions as good as new.



#### Static Wire

A small static wire in its wall which is to be grounded to the fitting to reduce the risk of a spark being generated by static electricity caused by the movement of the fuel.



#### Four finger grip bend restrictor

Oilsield fuel hose comes with four finger grip bend restrictor which increase the working efficiency of user. It reduce bending stress near the hose-coupling junction & prevent it from kinks.

## Variations

### Fuel Hose

Part No.	Inner Diameter (Inch)	Length (Feet)	Fittings (Inch)	Package Dimensions L x W x H (Inch)	Package Weight (Pounds)
OSFH3410	3/4	10	3/4 Male NPT	xx	
OSFH3412	3/4	12	3/4 Male NPT	xx	
OSFH3415	3/4	15	3/4 Male NPT	xx	
OSFH3420	3/4	20	3/4 Male NPT	xx	
OSFHOne10	1	10	3/4 Male NPT	xx	
OSFHOne12	1	12	3/4 Male NPT	xx	
OSFHOne15	1	15	3/4 Male NPT	xx	
OSFHOne20	1	20	3/4 Male NPT	xx	

## Product Images



This PDF was downloaded from the following URL  
<https://www.rmxind.com/hose/oilshield-fuel-hoses/?&region=north-america>  
 on Thursday, 29 January 2026

Scan QR Code on the right to access this URL in the browser.

