OilShield Fuel Hoses

RMX Oil Shield synthetic yarn farm fuel transfer hose assembly with static wire required for use with or 0 volt “Electric” pumps. 2X Kink Resistant and Flexible down to -30°F. Award Winning Formulation. Construction: oil resistant tube/cover. Spiral reinforced with synthetic yarn. Includes static wire built into hose wall.



Features

- 1 year warranty
- Nitro cover
- 8” Internal strain relief springs on each end to prevent kinking at the coupling
- 2x kink resistant than other fuel hoses
- RMA Class A oil-resistant tube & cover
- Static wire allows use with electric pumps
- Cold weather flexibility down to -30° F
- 100 PSI working pressure
- Ozone resistant
- Kink resistant
- For use where UL approval is not required

For use with diesel, gasoline, kerosene, biodiesel B10 and B20

1 Year	Class A Oil Resistant	100 PSI	-30°F
Warranty		Working Pressure	Temperature Range

Features at a glance



Internal strain relief springs

Internal strain relief springs eliminate your hose from kinking, crimping, and straining at the faucet. Heavy-duty spring coil allows your hose to bend but not kink, protecting your hose and faucet.



RMA Class A Oil-resistant

Oil-Shield fuel hose is perfect for work areas where oil, diesel, grease spillage is a concern. It can remain in constant contact with fuel & oil for months & functions as good as new.



Static Wire

A small static wire in its wall which is to be grounded to the fitting to reduce the risk of a spark being generated by static electricity caused by the movement of the fuel.



Four finger grip bend restrictor

Oilsield fuel hose comes with four finger grip bend restrictor which increase the working efficiency of user. It reduce bending stress near the hose-coupling junction & prevent it from kinks.

Copyright © 2026 RMX Industries. All rights reserved. Email: sales@rmxind.com | Website: https://www.rmxind.com

Variations

Fuel Hose

Part No.	Inner Diameter (Inch)	Length (Feet)	Fittings (Inch)	Package Dimensions L x W x H (Inch)	Package Weight (Pounds)
OSFH3410	3/4	10	3/4 Male NPT	x x	
OSFH3412	3/4	12	3/4 Male NPT	x x	
OSFH3415	3/4	15	3/4 Male NPT	x x	
OSFH3420	3/4	20	3/4 Male NPT	x x	
OSFHONE10	1	10	3/4 Male NPT	x x	
OSFHONE12	1	12	3/4 Male NPT	x x	
OSFHONE15	1	15	3/4 Male NPT	x x	
OSFHONE20	1	20	3/4 Male NPT	x x	

Product Images





This PDF was downloaded from the following URL
https://www.rmxind.com/hose/oilshield-fuel-hoses/?&region=north-america
on Tuesday, 03 November 2026

Scan QR Code on the right to access this URL in the browser.

Copyright © 2026 RMX Industries. All rights reserved. Email: sales@rmxind.com | Website: https://www.rmxind.com